

MAXWALD

A-4694 Ohlsdorf, Irresbergsstraße 1

Telefon 0043(0)7612/47219-0

Telefax 0043(0)7612/47219-9

www.maxwald.com

UNIMOG/TRUCK Winches 13A

RESCUE- and FORESTRY use / FRONT

Standard equipment:

- Mounting – Front Plate
- DISC BRAKE (Dead Man System)
- Powershift clutch with over-load-protection



Technical data / type	A 300 ME	A 500 ME	A516 ME
Pulling force (1st layer)	4,0to	6,0to	6,0to
Brake (Dead Man System)	DISC BRAKE	DISC BRAKE	DISC BRAKE
Cable capacity	70m/9mm	80m/11mm	130m/11mm
Cable with end-hook included	50m/9mm	80m/10mm	80m/10mm
Spooling device	-	-	automatic
Operation line	Serie	Serie	Serie
Price (driven by hydraulic-engine)**	Serie	Serie	Serie
OPTION:			
Electro-hydraulic operation Var. IV, remote control (independent oil supply, requirement for radio!)	---	OPTION	OPTION
Radio HBC Model „MAX“ complete incl. “SOFT-BRAKE”	---	OPTION	OPTION

* Not possible for all vehicles!

** Winches with hydraulic-drive about 1.0 to less pulling force, than PTO driven winches/models.
about 10m/min pulling speed (at idle gas)!

Requirement for hydraulic system:

A 300 ME – minimum 40 liters / 200 bar!

A500 ME; A516ME - minimum 75 liters / 200 bar!

PLEASE NOTE: Accurate drawings or mounting plate and if required catch hooks must be supplied!

PLEASE NOTE: Prices are indicative; can change according vehicle,...

Optional features: (see catalogue and price-list 12A)

Compacted forestry rope

Second cable in feed

Hydraulic operation for clutch/Var. 0

Cable in feed brake (mechanical)

Hydraulic brake for cable in / out operation